

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
10 June 2004 (10.06.2004)

PCT


(10) International Publication Number  
**WO 2004/048159 A1**

- (51) International Patent Classification<sup>7</sup>: **B60R 21/34**
- (21) International Application Number:  
PCT/SE2003/001823
- (22) International Filing Date:  
26 November 2003 (26.11.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
0227809.1 28 November 2002 (28.11.2002) GB
- (71) Applicant (for all designated States except US): **AUTO-LIV DEVELOPMENT AB** [SE/SE]; S-447 83 Vårgårda (SE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **HAGLUND, Lennart** [SE/SE]; Korsnåbbsgatan 5, S-447 32 Vårgårda (SE).
- (74) Agent: **MEULLER, Erik**; Autoliv Development AB, S-447 83 Vårgårda (SE).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: IMPROVEMENTS IN OR RELATING TO A SAFETY ARRANGEMENT

(57) **Abstract:** A lifting unit (1) to lift the rear part of a hood or bonnet in the event that an accident should arise comprises an inner cylindrical guide (2) to receive gas from a gas generator and telescopically mounted on the guide, to telescopically interconnected cylindrical piston elements (12, 17). There is a certain degree of play between the telescopically interconnected units to facilitate a virtual pivoting movement of the hood or bonnet to be lifted by the lifting unit.





**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*